PATENT Docket No.: FR000003 Customer No. 000024737

## **Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

## **Listing of Claims:**

 (currently amended) An image processing method for providing threedimensional geometric modeling of the spine, using a biplanar image reconstruction, comprising:

acquiring a first digital view (F) of a part of the spine;

acquiring a second <u>digital</u> view (L) of the same part of the spine taken from a different angle around the longitudinal axis of the spine;

drawing an axial line (FAL, LAL) coinciding with a virtual axial line in a respective one of the first and second digital views, wherein drawing includes using a control means of a drawing program, and wherein each axial line (FAL,LAL) corresponds to a piece-wise linear curve drawn from a start point to an end point;

matching the dimensions of the <u>digital</u> views (F,L) from two predetermined corresponding landmarks (P1, P2) on each view, <u>wherein matching includes estimating a scale factor and a translation factor to make a system of coordinates for each view coincide, to provide a unique system of coordinates for the first and second digital views;</u>

performing a spline calculation for providing to provide a smoothed axial line (FAC, LAC) on each digital view, the spline calculation including mathematical modeling of the drawn piece-wise linear curves on a respective one of the first and second digital views, previously set by a control means of a drawing program, for supplying respective new digital smoothed curves, the new digital smoothed curves being constructed with interpolated values provided between points of the respective piece-wise linear curves, the new digital smoothed curves corresponding to a respective smoothed axial line

Page 2 of 11

p.6

Docket No.: FR000003 Customer No. 000024737

(FAC, LAC) on each view; and

deriving three-dimensional coordinates (z, x, y) of corresponding points (P) along the spine as a function of the smoothed axial lines (FAC, LAC).

- 2. (previously presented) The image processing method as claimed in Claim 1, wherein, for matching the two views, an axial line (FAL, LAL) is drawn on the spine on each view, and the two landmarks (P1, P2) are set on said axial line on each view.
- 3. (previously presented) The image processing method as claimed in claim 2, wherein the matching of the dimensions of the two views is performed by a calculating matching coordinates  $[(x_{F1}, z_{F1}), (y_{L1}, z_{L1}); (x_{F2}, z_{F2}), (y_{L2}, z_{L2})]$  for the two corresponding landmarks (P1, P2).
- 4. (previously presented) The image processing method as claimed in Claim 3, wherein a common system of coordinates (Z, X, Y) is determined for the two views, from the matched coordinates of the two corresponding landmarks.
- 5. (cancelled)
- (previously presented) The image processing method as claimed in Claim 2. 6. wherein three-dimensional coordinates (z, x, y) of corresponding points along the spine are determined for points (P) regularly spaced along the axis of coordinates (Z) corresponding to the longitudinal axis of the spine.
- 7. (previously presented) The image processing method as claimed in Claim 2, wherein the common system of coordinates is an orthogonal system, the first view is a frontal view (F), the second view is a lateral view (L) orthogonal to the frontal view, with a common axis (Z) in the direction of the longitudinal axis of the spine, a second axis

Page 3 of 11



Docket No.: FR000003 Customer No. 000024737

(X) parallel to the frontal plane of view and the third axis (Y) parallel to the lateral plane of view.

- (previously presented) An imaging system having acquisition means for acquiring 8. a first and a second view of the spine, having display means to display the two views of the spine, having drawing means to draw axial lines of the spine and to set predetermined corresponding landmarks on each view and having processing means to calculate three-dimensional coordinates of points along the spine according to the method as claimed in Claim 1.
- 9. (previously presented) The imaging system as claimed in Claim 8, wherein the processing means comprise a suitably programmed computer of at least one selected from the group consisting of a workstation and a special purpose processor having circuit means, which are arranged to process image data according to the method as claimed in Claim 1, and wherein the display means display images processed according to said method, further comprising means to store the image data.
- 10. (previously presented) An X-ray examination apparatus having a system as claimed in Claim 8.
- 11. (previously presented) A computer program product comprising a set of instructions for carrying out the method as claimed in Claim 1.